

# **Material Safety Data Sheet**

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** 3M(tm) 4314, 4317, & 4318 URETHANE FOAM TAPES. **MANUFACTURER:** 3M

DIVISION: Industrial Tape And Specialties Division

ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 08/06/2004 **Supercedes Date:** 08/06/2004

**Document Group:** 19-4441-2

#### **Product Use:**

General Use:

3M(TM) Urethane Foam Tape Series 4300 is used to seal lighting fistures, doors, windows, and cabinets and can also be used to help cushion, damp sound, and absorb vibration.

### **SECTION 2: INGREDIENTS**

Ingredient	
POLYURETHANE-ESTER FOAM	
ACRYLATE POLYMER	
CHARCOAL GRAY COLOR	
ISOOCTYL ACRYLATE	

 C.A.S. No.
 % by Wt

 TRADE SECRET
 43 - 76

 TRADE SECRET
 21 - 56

 TRADE SECRET
 0.75 - 5

 29590-42-9
 0 - 1.5

## **SECTION 3: HAZARDS IDENTIFICATION**

### **3.1 EMERGENCY OVERVIEW**

**Specific Physical Form:** Roll of Tape **Odor, Color, Grade:** black color, slight acrylate odor.

### General Physical Form: Solid

**Immediate health, physical, and environmental hazards:** This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

## 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

No health effects are expected.

**Skin Contact:** No health effects are expected.

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Ingestion:**

No health effects are expected.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** No need for first aid is anticipated.

Skin Contact: No need for first aid is anticipated.

**Inhalation:** No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL OSHA Flammability Classification: No Data Available Not Applicable Not Applicable Not Applicable Not Applicable

### 5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire. Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Nonflammable. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** None inherent in this product. No unusual fire or explosion hazards are anticipated. Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Accidental Release Measures: Not applicable. Ventilate the area with fresh air.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment.

### 7.2 STORAGE

Store under normal warehouse conditions. Not applicable.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1 ENGINEERING CONTROLS

General ventilation adequate below 400 C. Local exhaust recommended above 400 C. Not applicable.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Not applicable.

#### 8.2.2 Skin Protection

Gloves are not required. Not applicable. Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

#### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not ingest. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Not applicable.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
ISOOCTYL ACRYLATE	3M	TWA	5 ppm	
ISOOCTYL ACRYLATE	AIHA	TWA	5 ppm	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form:	Roll of Tape
Odor, Color, Grade:	black color, slight acrylate odor.
General Physical Form:	Solid
Autoignition temperature	No Data Available
Flash Point	Not Applicable
Flammable Limits - LEL	Not Applicable
Flammable Limits - UEL	Not Applicable
Boiling point	Not Applicable
Vapor Density	Not Applicable
Vapor Pressure	Not Applicable
Specific Gravity	Not Applicable
pH	Not Applicable
Melting point	No Data Available
Solubility In Water	Not Applicable
Evaporation rate	Not Applicable
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Viscosity	Not Applicable

# **SECTION 10: STABILITY AND REACTIVITY**

### Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide Condition Not Specified Not Specified

Hydrogen Chloride

Not Specified

**Hazardous Decomposition:** Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

# SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not determined. Not applicable.

## CHEMICAL FATE INFORMATION

Not determined. Not applicable.

# SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Agglomerate and send to sanitary landfill. Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility.

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

## **US FEDERAL REGULATIONS**

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

## **INTERNATIONAL REGULATIONS**

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### HMIS Hazard Classification Health: 0 Flammability: 0 Reactivity: 0 Protection: A

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information. Correct typographical error in Trade Name.

Revision Changes: Section 1: Product name was modified. Page Heading: Product name was modified. Section 1: Initial issue message was modified. Section 16: Reason for reissue comment was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

### 3M MSDSs are available at www.3M.com