MATERIAL SAFETY 3M

DATA SHEET 3M Center

St. Paul, Minnesota

55144-1000

1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 1998, Minnesota Mining and Manufacturing Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that:

- 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

DIVISION: BONDING SYSTEMS DIVISION TRADE NAME:

NO. 4926, 4936, 4941 AND 4956 ACRYLIC FOAM TAPES (INCLUDING "F" SERIES FILM LINERED TAPES

ID NUMBER/U.P.C.:

```
70-0000-6238-3 00-21200-94223-5 70-0000-7970-0 00-21200-94847-3
70-0000-7971-8 00-21200-94848-0 70-0000-7972-6 00-21200-94849-7
70-0000-8286-0 -
                                                                         - - 70-0000-8287-8 -
70-0000-8288-6
                                                                                                                70-0000-8289-4
70 - 0061 - 4723 - 8 \quad 00 - 21200 - 64604 - 1 \quad 70 - 0061 - 4724 - 6 \quad 00 - 21200 - 64605 - 8 \\
70 - 0061 - 4725 - 3 \\ 00 - 21200 - 64606 - 5 \\ 70 - 0061 - 4736 - 0 \\ 00 - 21200 - 64617 - 1
70-0061-4737-8 00-21200-64618-8 70-0061-4739-4 00-21200-64620-1
                                                                                                                70-0061-4738-6 00-21200-64619-5
                                                                                                                70-0061-4740-2 00-21200-64621-8
70-0061-4746-9 00-21200-64627-0
                                                                                                                70-0061-4747-7 00-21200-64628-7
70 - 0061 - 4748 - 5 \quad 00 - 21200 - 64629 - 4 \quad 70 - 0061 - 4749 - 3 \quad 00 - 21200 - 64630 - 0 \\
70 - 0061 - 4750 - 1 \qquad 00 - 21200 - 64631 - 7 \qquad 70 - 0061 - 4982 - 0 \qquad 00 - 21200 - 64886 - 1
70-0061-4983-8 00-21200-64887-8 70-0061-4984-6 00-21200-64888-5
70-0160-4234-6 00-21200-84035-7 70-0160-5041-4 00-21200-23727-0
70-0160-5042-2 00-21200-64554-9 70-0160-5043-0 00-21200-64555-6
70 - 0160 - 5417 - 6 \quad 00 - 21200 - 23048 - 6 \quad 70 - 0160 - 5433 - 3 \quad 00 - 21200 - 23047 - 9
70 - 0160 - 5449 - 9 \quad 00 - 21200 - 23046 - 2 \quad 70 - 0160 - 5457 - 2 \quad 00 - 21200 - 23045 - 5 \quad 00 - 21200 - 23045 - 5
```

ISSUED: March 09, 1998

SUPERSEDES: February 24, 1997

DOCUMENT: 06-2282-9

 ${\tt MSDS:\ NO.\ 4926,\ 4936,\ 4941\ AND\ 4956\ ACRYLIC\ FOAM\ TAPES\ (INCLUDING\ "F")}$ 

SERIES FILM LINERED TAPES March 09, 1998

SERIES FILM LINERED TAPES					
March 09, 1998				PAGE	2
1. INGREDIENT	C.A.S. NO.		PERCENT		
ACRYLATE POLYMER WITH GLASS AND SILICA					
FILLERS	9017-68-9	70	- 95		
ACRYLATE TERPOLYMER	Unknown	6	- 27		
CARBON	1333-86-4	1	- 5		
2. PHYSICAL DATA					
BOILING POINT:					
VAPOR PRESSURE:					
VAPOR DENSITY:					
SOLUBILITY IN WATER: N/A					
SPECIFIC GRAVITY: ca9 Wat	ter=1				
PERCENT VOLATILE:					
pH:N/A					
VISCOSITY:					
APPEARANCE AND ODOR: Film, Gray, Slight Acrylate Odor					
3. FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT:					
EXTINGUISHING MEDIA: Water, Water spray, Carbon dioxide, Dry	chemical, Dry	powde	r, Foam		
SPECIAL FIRE FIGHTING PROCEDURES: None known.					
UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards are	e anticipated.				
NFPA HAZARD CODES: HEALTH: 0 FIRE: 1 REUNUSUAL REACTION HAZAR					
OSHA FIRE HAZARD CLASS: Not applicable					

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

SERIES FILM LINERED TAPES

March 09, 1998 PAGE 3

\_\_\_\_\_\_

#### 4. REACTIVITY DATA

\_\_\_\_\_

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide.

\_\_\_\_\_\_

## 5. ENVIRONMENTAL INFORMATION

-----

#### SPILL RESPONSE:

Observe precautions from other sections. Collect spilled material.

#### RECOMMENDED DISPOSAL:

Dispose of waste product in a sanitary landfill. Disposal alternative: Incinerate in an industrial or commercial facility in the presence of a combustible material.

#### ENVIRONMENTAL DATA:

Not determined.

# REGULATORY INFORMATION:

Volatile Organic Compounds: N/A. VOC Less H2O & Exempt Solvents: N/A.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: No CHRONIC: No

\_\_\_\_\_\_

#### 6. SUGGESTED FIRST AID

-----

## EYE CONTACT:

No need for first aid is anticipated.

## SKIN CONTACT:

No need for first aid is anticipated.

-----

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

SERIES FILM LINERED TAPES

March 09, 1998 PAGE 4

\_\_\_\_\_\_

6. SUGGESTED FIRST AID (continued)

\_\_\_\_\_\_

#### INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

### IF SWALLOWED:

No need for first aid is anticipated.

\_\_\_\_\_

#### 7. PRECAUTIONARY INFORMATION

\_\_\_\_\_\_

#### EYE PROTECTION:

Not applicable.

#### SKIN PROTECTION:

Avoid prolonged or repeated skin contact.

#### RECOMMENDED VENTILATION:

Provide appropriate local exhaust when product is heated.

## RESPIRATORY PROTECTION:

Avoid breathing of thermal decomposition products.

# PREVENTION OF ACCIDENTAL INGESTION:

Not applicable.

# RECOMMENDED STORAGE:

Not applicable.

## FIRE AND EXPLOSION AVOIDANCE:

Not applicable.

### EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH SKIN*
ACRYLATE POLYMER WITH GLASS AND				
SILICA FILLERS	NONE	NONE	NONE	NONE
ACRYLATE TERPOLYMER	NONE	NONE	NONE	NONE
CARBON	3.5	MG/M3	TWA	ACGIH
CARBON	3.5	MG/M3	TWA	OSHA

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

# SOURCE OF EXPOSURE LIMIT DATA:

-----

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

SERIES FILM LINERED TAPES

March 09, 1998 PAGE 5

EXPOSURE LIMITS (continued)

INGREDIENT VALUE UNIT TYPE AUTH SKIN\*

-----

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration

- NONE: None Established

\_\_\_\_\_

# 8. HEALTH HAZARD DATA

-----

#### EYE CONTACT:

Eye contact is not expected to occur during normal use of the product.

## SKIN CONTACT:

Mechanical skin irritation: signs/symptoms can include itching and redness.

#### TNHATATTON:

Health effects from inhalation are not expected unless product is heated.

Vapors of heated material may cause respiratory system irritation.

This product may have a characteristic odor; however, no adverse health effects are anticipated.

# IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

# OTHER HEALTH HAZARD INFORMATION:

Exposure to this material in normal storage and handling has not been reported to cause significant adverse health effects. However, under normal processing conditions, e.g. grinding or heating, this product may release fumes and vapors of variable composition based on specific process conditions. These process releases may produce irritation or any of the health effects listed above when the emissions are present at elevated concentrations. Use with appropriate local exhaust ventilation.

\_\_\_\_\_\_

## SECTION CHANGE DATES

\_\_\_\_\_\_

HEADING

SECTION CHANGED SINCE February 24, 1997 ISSUE

SERIES FILM LINERED TAPES

March 09, 1998 PAGE 6

-----

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.