



Polyurethane Protective Tape

8562

Technical Data

July 2003

Product Description

3M™ Polyurethane Protective Tape 8562 (indoor grade) is made from an abrasion resistant polyurethane elastomer that resists puncture, tearing, abrasion and erosion. Polyurethane Protective Tape 8562 provides a simple, easy, and fast method of protecting a surface from corrosion, abrasion, erosion and minor impact damage. Polyurethane Protective Tape 8562 is constructed with a long-aging, solvent resistant, pressure sensitive, acrylic adhesive, protected with an easy-release paper liner.

Polyurethane Protective Tape 8562 is a transparent tape available with a paper liner only.

Typical Physical Properties and Performance Characteristics

- Notes: 1) The following technical information and data should be considered representative or typical only and should not be used for specification purposes. Metric values are listed in parenthesis.
- 2) ASTM = American Society for Testing and Materials.
- 3) Metric values are listed in parenthesis.

A. Dimensions:

Approximate Applied Thickness*:	0.006 inch (0.15mm) film 0.002 inch (0.05 mm) adhesive Total thickness 0.008 (0.20mm)
Standard Roll Length:	36 yd (32.9m)
Available Widths:	1/2-inch min. to 48-inch max. (1.25 cm to 122 cm)
Approximate Weight: *	0.44 lb./yd ² (220 g/m ²)

*Excludes the paper liner that is removed from the tape prior to application.

B. Typical Physical Properties and Performance Characteristics

PROPERTY	TEST METHOD	UNITS	TYPICAL VALUE
Tensile Strength @ Break	ASTM D882	lb./ in (N/100 mm)	40 (700)
Elongation % @ Break	ASTM D882	%	400
Peel Adhesion @ 70°F (21°C) to: Bare Aluminum Acrylic Enamel paint ABS Plastic	ASTM D-1000	oz./ in (N/100 mm)	56 (61) 39 (42) 46 (50)
Max. Service Temperature		F°(C°)	275°F (135°C)

3M Technical Data

Polyurethane Protective Tape 8562

General Information	<ul style="list-style-type: none"> 3M™ Polyurethane Protective Tape has environmental resistance properties and has been used to isolate and protect substrates from environmental damage and corrosive elements. Polyurethane Protective Tape may be painted per 3M Technical Bulletin Polyurethane Protective Tape, Paint Instructions (70-0702-6358-0). 																
Environmental, Health and Safety	<ul style="list-style-type: none"> Polyurethane Protective Tape is 100% solids and contains no hazardous air pollutants (HAPs), volatile organic components (VOCs) or materials restricted by regulations or law. Respiratory protection is not required under normal use conditions. Polyurethane Protective Tape meets US Federal and California regulations for landfillable materials. The product is potentially recyclable. Packaging materials meet US Federal and California regulations for landfillable materials and are recyclable or reusable. This product is considered to be an article that does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. 																
Shipping and Storage	<p>No special/hazardous labeling or packaging required and no regulations for air, ground or water shipment for this product.</p> <p>Keep film in a clean area away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton.</p> <p>Shelf life: Two (2) years from date of manufacture.</p>																
Precautionary Information	<p>Refer to product label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.</p>																
For Additional Information	<p>To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550. Address correspondence to: 3M Aerospace and Aircraft Maintenance Division, 3M Center, Building 220-9W-14, St. Paul, MN 55144-1000. Our fax number is 651-737-2275. If you are outside of the US, please contact your nearest 3M office or one of the following branches:</p>																
	<table border="0"> <tr> <td>Australia 61-2-498-9711 tel 61-2-498-9710 fax</td> <td>Austria 01-86686-298 tel 01-86686-229 fax</td> <td>Canada 800-410-6880 ext. 6018 tel 800-263-3489 fax</td> <td>China 86-21-62753535 tel 86-21-62190698 fax</td> </tr> <tr> <td>France 30-31-6234 tel 30-31-6195 fax</td> <td>Germany 02131-14-2344 tel 02131-14-3647 fax</td> <td>Italy 02-7035-2177 tel 02-7035-2125 fax</td> <td>Japan 03-3709-8245 tel 03-3709-8743 fax</td> </tr> <tr> <td>Korea 02-3771-4114 tel 02-786-7429 fax</td> <td>Netherlands 31-71-5-450-272 tel 31-71-5-450-280 fax</td> <td>South Africa 11-922-9111 tel 11-922-2116 fax</td> <td>Switzerland 01-724-9114 tel 01-724-9068 fax</td> </tr> <tr> <td></td> <td></td> <td></td> <td>United Kingdom (0) 161-237-6174 tel (0) 161-237-3371 fax</td> </tr> </table>	Australia 61-2-498-9711 tel 61-2-498-9710 fax	Austria 01-86686-298 tel 01-86686-229 fax	Canada 800-410-6880 ext. 6018 tel 800-263-3489 fax	China 86-21-62753535 tel 86-21-62190698 fax	France 30-31-6234 tel 30-31-6195 fax	Germany 02131-14-2344 tel 02131-14-3647 fax	Italy 02-7035-2177 tel 02-7035-2125 fax	Japan 03-3709-8245 tel 03-3709-8743 fax	Korea 02-3771-4114 tel 02-786-7429 fax	Netherlands 31-71-5-450-272 tel 31-71-5-450-280 fax	South Africa 11-922-9111 tel 11-922-2116 fax	Switzerland 01-724-9114 tel 01-724-9068 fax				United Kingdom (0) 161-237-6174 tel (0) 161-237-3371 fax
Australia 61-2-498-9711 tel 61-2-498-9710 fax	Austria 01-86686-298 tel 01-86686-229 fax	Canada 800-410-6880 ext. 6018 tel 800-263-3489 fax	China 86-21-62753535 tel 86-21-62190698 fax														
France 30-31-6234 tel 30-31-6195 fax	Germany 02131-14-2344 tel 02131-14-3647 fax	Italy 02-7035-2177 tel 02-7035-2125 fax	Japan 03-3709-8245 tel 03-3709-8743 fax														
Korea 02-3771-4114 tel 02-786-7429 fax	Netherlands 31-71-5-450-272 tel 31-71-5-450-280 fax	South Africa 11-922-9111 tel 11-922-2116 fax	Switzerland 01-724-9114 tel 01-724-9068 fax														
			United Kingdom (0) 161-237-6174 tel (0) 161-237-3371 fax														
Important Notice	<p>3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.</p>																
Limitation of Remedies And Liability	<p>If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.</p>																



This product was manufactured under a 3M quality system registered to ISO 9001 standards.

For Additional Product Safety and Health Information, See Material Safety Data Sheet.

3M
 Transportation Business
 Aerospace & Aircraft Maintenance Division

3M Center, Building 220-9W-14
 St. Paul, MN 55144-1000
 www.3M.com/aerospace

Printed in U.S.A.
 ©3M 2003 60-9700-0046-3